C　無線ＬＡＮコントローラは、300台程度の無線ＬＡＮアクセスポイントを管理可能な性能を有すること。
D　無線ＬＡＮコントローラは、本学既設の無線ＬＡＮアクセスポイントを含めて全てを集中管理できること。または、既存の無線ＬＡＮアクセスポイントをすべて導入する無線ＬＡＮコントローラで利用可能な無線ＬＡＮアクセスポイントに置き換えること。
E　無線ＬＡＮアクセスポイントは、本学設置のキャンパスネットワークフロアスイッチからPoE受電で動作すること。
F　無線ＬＡＮアクセスポイントは、2.4GHz帯と５GHz帯の通信を同時に提供すること。
G　無線ＬＡＮアクセスポイントは、マルチＳＳＩＤに対応していること。同時に2.4GHz帯、５GHz帯それぞれで複数のＳＳＩＤを同時に送出できること。
H　接続される無線ＬＡＮクライアントの状況をモニタし、管理用ツールから確認できること。これを用いた運用管理ツールを提供すること。
I　ユーザ認証のために本学が運用するＲＡＤＩＵＳサーバと連携可能であること。
J　本学が運用する高セキュリティリスク端末の自動遮断システムと連携できること。

2　資料及びコメントの提供方法　上記１⑵の物品に関する一般的な参考資料及び同⑸の要求要件等に関するコメント並びに提供可能なライブラリーに関する資料等の提供を招請する。
⑴　資料等の提供期限　令和２年５月１日17時00分（郵送の場合は必着のこと。）
⑵　提供先　〒183―8538 東京都府中市晴見町３－８－１　東京農工大学財務課契約係長　中津井琢磨　電話042―367―5525
3　説明書の交付　本公表に基づき応募する供給者に対して導入説明書を交付する。
⑴　交付期間　令和２年３月26日から令和２年５月１日まで。
⑵　交付場所　上記２⑵に同じ。
4　説明会の開催　本公表に基づく導入説明会を開催する。
⑴　開催日時　令和２年４月３日15時00分
⑵　開催場所　東京農工大学工学府管理棟３階第２会議室
5　その他　この導入計画の詳細は導入説明書による。なお、本公表内容は予定であり、変更することがあり得る。
6　Summary
⑴　Classification of the products to be procured : 14
⑵　Nature and quantity of the products to be rent : The Wireless LAN System 1 Set
⑶　Type of the procurement : Rent
⑷　Basic requirements of the procurement :
A　This system must provide the Wireless Access Points.
B　This system must consist from the Wireless LAN Controller for central management of the Wireless Access Points. The Wireless LAN Controller may be in the on-premise system or the cloud-based system.
C　The Wireless Controller should have a capability for managing at least 300 Wireless Access Points.
D　The Wireless Controller should manage all existing Wireless Access Points in our university. Otherwise, the system should replace all existing Wireless Access Points in our university, which is capable for the Wireless LAN Controller.
E　The Wireless Access Points should work by PoE power supply with existing Campus Network Floor Switches in our university.
F　The Wireless Access Points should have a capability for connection in 2.4GHz band and 5GHz band wireless communication simultaneously.
G　The Wireless Access Points should have a multiple SSID function. TheWireless Access Points should transmit multiple SSIDs in 2.4GHz band and 5GHz band wireless communication simultaneously.
H　The system should provide the management and visualization tool formonitoring the Wireless LAN Clients in Wireless Network.
I　The system should work together with the RADIUS server in our university.
J　The system should work together with the Security Measure System by Automatic Isolation of High-level security risk clients in ouruniversity.
⑸　Time limit for the submission of the requested material : 17 : 00　1 May, 2020
⑹　Contact point for the notice : Takuma Nakatsui, Section Chief for Contract and Purchase Section, Financial Affairs Office, Tokyo University of Agriculture and Technology, 3―8―1 Harumi-cho, Fuchu-shi, Tokyo 183―8538 Japan, TEL 042―367―5525

資料提供招請に関する公表

次のとおり物品の導入を予定していますので、当該導入に関して資料等の提供を招請します。
令和２年３月26日
国立大学法人名古屋大学
財務担当理事　木村　彰吾
◎調達機関番号　415　◎所在地番号　23
○第５号
1　調達内容
⑴　品目分類番号　22、31
⑵　導入計画物品及び数量　循環器血管造影診断システム　一式
⑶　調達方法　購入等
⑷　導入予定時期　令和２年度10月以降
⑸　調達に必要とされる基本的な要求要件
A　Ｘ線血管撮影装置はフラットパネル搭載型であること。
B　Ｘ線血管撮影装置は、２つのＸ線管を搭載していること。
C　頭部、胸部、腹部をはじめとする全身のＩＶＲに対応したシステムであること。
D　血管内治療および不整脈治療を支援する機能や解析装置を有すること。
E　Ｘ線被曝を低減する機能を有すること。
F　既存の病院情報システムならびに部門システムとの連携ができること。
G　患者情報保護のため、セキュリティ対策及びシステムダウン対策が施されていること。
H　システムは、災害による停電・浸水への対策が施されていること。

2　資料及びコメントの提供方法　上記１⑵の物品に関する一般的な参考資料及び同⑸の要求要件等に関するコメント並びに提供可能なライブラリーに関する資料等の提供を招請する。
⑴　資料等の提供期限　令和２年５月11日16時00分（郵送の場合は必着のこと。）
⑵　提供先　〒466―8560 名古屋市昭和区鶴舞町65　名古屋大学医学部・医学系研究科経理課調達グループ　水谷　真夕　電話052―744―2433
3　説明書の交付　本公表に基づき応募する供給者に対して導入説明書を交付する。
⑴　交付期間　令和２年３月26日から令和２年５月11日まで。
⑵　交付場所　上記２⑵に同じ。
4　説明会の開催　本公表に基づく導入説明会を開催する。
⑴　開催日時　令和２年３月30日16時00分
⑵　開催場所　名古屋大学医学部附属病院中央診療棟Ａ　３階会議室
5　その他　この導入計画の詳細は導入説明書による。なお、本公表内容は予定であり、変更することがあり得る。
6　Summary
⑴　Classification of the products to be procured : 22, 31
⑵　Nature and quantity of the products to be purchased : X-ray angiography system with flat panel detectors 1 Set
⑶　Type of the procurement : Purchase
⑷　Basic requirements of the procurement :
A　The X-ray angiography device must be flat panel detector mounted type.
B　The X-ray angiography device must be two X-ray tubes.
C　This system must be able to support whole body IVR including head, chest, and abdomen.
D　This system must have functions and analysis devices to support intravascular treatment and catheter ablation.
E　This system must have functions to reduce X-ray exposure.