```
        rdnSequence  RDNSequence
}

RDNSequence ::= SEQUENCE OF RelativeDistinguishedName

RelativeDistinguishedName ::= SET SIZE (1 .. MAX) OF AttributeTypeAndValue

ID ::= OBJECT IDENTIFIER

ATTRIBUTE ::= CLASS {
        &Type,
        &id     OBJECT IDENTIFIER UNIQUE }
WITH SYNTAX {
        WITH SYNTAX &Type
        ID          &id }

SupportedAttributes ATTRIBUTE ::= {
        commonName | organizationName |   -- RelativeDistinguishedName attributes
        timeLimit | suspensionSecretCode  -- regInfo attributes
}

commonName ATTRIBUTE ::= {
        WITH SYNTAX        DirectoryString {ub-common-name}
        ID                 id-at-commonName }

organizationName ATTRIBUTE ::= {
        WITH SYNTAX        DirectoryString {ub-organization-name}
        ID                 id-at-organizationName }

DirectoryString { INTEGER:maxSize } ::= CHOICE {
        printableString         PrintableString (SIZE (1..maxSize)),
        utf8String              UTF8String (SIZE(1..maxSize))
}

timeLimit ATTRIBUTE ::= {
        WITH SYNTAX        TimeLimit
        ID                 id-registeredcert-mg-effectiveTimeLimit }

TimeLimit ::= OCTET STRING

suspensionSecretCode ATTRIBUTE ::= {
        WITH SYNTAX        SuspensionSecretCode
        ID                 id-registeredcert-mg-suspensionSecretCode }

SuspensionSecretCode ::= SEQUENCE {
      hashAlg                   AlgorithmIdentifier,
      hashedSecretCode          OCTET STRING
}

id-at OBJECT IDENTIFIER ::= {joint-iso-ccitt(2) ds(5) 4}

id-at-commonName              OBJECT IDENTIFIER ::= {id-at 3}
id-at-organizationName        OBJECT IDENTIFIER ::= {id-at 10}

id-registeredcert OBJECT IDENTIFIER ::= { 1 2 392 100300 1 }

id-registeredcert-mg OBJECT IDENTIFIER ::= { id-registeredcert 2 }

id-registeredcert-mg-effectiveTimeLimit OBJECT IDENTIFIER ::= { id-registeredcert-mg 104 }
id-registeredcert-mg-suspensionSecretCode OBJECT IDENTIFIER ::= {
    id-registeredcert-mg 105 }

ub-common-name               INTEGER ::= 64
ub-organization-name         INTEGER ::= 64

END
```

２　Implicitly Tagged Module

```
MOJCRMFRegistration { 1 2 392 100300 1 4 42 }

DEFINITIONS IMPLICIT TAGS ::=
BEGIN

IMPORTS
        AttributeTypeAndValue, AlgorithmIdentifier, Name,
        SubjectPublicKeyInfo, Extensions, DirectoryString, EXTENSION
        FROM MOJCMPRegistration { 1 2 392 100300 1 4 41 };


CertReqMessages ::= SEQUENCE SIZE (1..MAX) OF CertReqMsg

CertReqMsg ::= SEQUENCE {
    certReq   CertRequest,
    pop       ProofOfPossession  OPTIONAL,
    regInfo   SEQUENCE SIZE(1..MAX) OF AttributeTypeAndValue }

CertRequest ::= SEQUENCE {
    certReqId     INTEGER,
    certTemplate  CertTemplate }

CertTemplate ::= SEQUENCE {
```