SECTION B – MANAGEMENT AND CONTROL REQUIREMENTS FOR SHIPS

Regulation B-1
Ballast Water Management Plan

Each ship shall have on board and implement a Ballast Water Management plan. Such a plan shall be approved by the Administration taking into account Guidelines developed by the Organization. The Ballast Water Management plan shall be specific to each ship and shall at least:

1 detail safety procedures for the ship and the crew associated with Ballast Water Management as required by this Convention;

2 provide a detailed description of the actions to be taken to implement the Ballast Water Management requirements and supplemental Ballast Water Management practices as set forth in this Convention;

3 detail the procedures for the disposal of Sediments:

.1 at sea; and

.2 to shore;

4 include the procedures for coordinating shipboard Ballast Water Management that involves discharge to the sea with the authorities of the State into whose waters such discharge will take place;

5 designate the officer on board in charge of ensuring that the plan is properly implemented;

6 contain the reporting requirements for ships provided for under this Convention; and

7 be written in the working language of the ship. If the language used is not English, French or Spanish, a translation into one of these languages shall be included.

Regulation B-2
Ballast Water Record Book

1 Each ship shall have on board a Ballast Water record book that may be an electronic record system, or that may be integrated into another record book or system and which shall at least contain the information specified in Appendix II.

2 Ballast Water record book entries shall be maintained on board the ship for a minimum period of two years after the last entry has been made and thereafter in the Company's control for a minimum period of three years.

3 In the event of the discharge of Ballast Water pursuant to regulations A-3, A-4 or B-3.6 or in the event of other accidental or exceptional discharge of Ballast Water not otherwise exempted by this Convention, an entry shall be made in the Ballast Water record book describing the circumstances of, and the reason for, the discharge.

4 The Ballast Water record book shall be kept readily available for inspection at all reasonable times and, in the case of an unmanned ship under tow, may be kept on the towing ship.

5 Each operation concerning Ballast Water shall be fully recorded without delay in the Ballast Water record book. Each entry shall be signed by the officer in charge of the operation concerned and each completed page shall be signed by the master. The entries in the Ballast Water record book shall be in a working language of the ship. If that language is not English, French or Spanish the entries shall contain a translation into one of those languages. When entries in an official national language of the State whose flag the ship is entitled to fly are also used, these shall prevail in case of a dispute or discrepancy.

6 Officers duly authorized by a Party may inspect the Ballast Water record book on board any ship to which this regulation applies while the ship is in its port or offshore terminal, and may make a copy of any entry, and require the master to certify that the copy is a true copy. Any copy so certified shall be admissible in any judicial proceeding as evidence of the facts stated in the entry. The inspection of a Ballast Water record book and the taking of a certified copy shall be performed as expeditiously as possible without causing the ship to be unduly delayed.

Regulation B-3
Ballast Water Management for Ships

1 A ship constructed before 2009:

.1 with a Ballast Water Capacity of between 1,500 and 5,000 cubic metres, inclusive, shall conduct Ballast Water Management that at least meets the standard described in regulation D-1 or regulation D-2 until 2014, after which time it shall at least meet the standard described in regulation D-2;

.2 with a Ballast Water Capacity of less than 1,500 or greater than 5,000 cubic metres shall conduct Ballast Water Management that at least meets the standard described in regulation D-1 or regulation D-2 until 2016, after which time it shall at least meet the standard described in regulation D-2.

2 A ship to which paragraph 1 applies shall comply with paragraph 1 not later than the first intermediate or renewal survey, whichever occurs first, after the anniversary date of delivery of the ship in the year of compliance with the standard applicable to the ship.

3 A ship constructed in or after 2009 with a Ballast Water Capacity of less than 5,000 cubic metres shall conduct Ballast Water Management that at least meets the standard described in regulation D-2.

4 A ship constructed in or after 2009, but before 2012, with a Ballast Water Capacity of 5,000 cubic metres or more shall conduct Ballast Water Management in accordance with paragraph 1.2.