CN 2017	Description	Base rate	Category	Note	1st year	2nd year	3rd year	4th year	5th year	6th year	7th year	8th year	9th year	10th year	11th year	12th year	13th year	14th year	As from 15th year
8415 10	- Of a kind designed to be fixed to a window, wall, ceiling or floor, self-contained or "split-system"																		
8415 10 90	-- Split-system	2.5 %	B3		1.3 %	0.6 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
	- Other																		
8415 81 00	-- Incorporating a refrigerating unit and a valve for reversal of the cooling/heat cycle (reversible heat pumps)	2.7 %	B3		1.4 %	0.7 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8427	Fork-lift trucks; other works trucks fitted with lifting or handling equipment																		
8427 20	- Other self-propelled trucks																		
	-- With a lifting height of 1 m or more																		
8427 20 19	--- Other	4.5 %	B3		2.3 %	1.1 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8431	Parts suitable for use solely or principally with the machinery of headings 8425 to 8430																		
8431 20 00	- Of machinery of heading 8427	4.0 %	B3		2.0 %	1.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8456	Machine tools for working any material by removal of material, by laser or other light or photon beam, ultrasonic, electrodischarge, electrochemical, electron beam, ionic-beam or plasma arc processes; water-jet cutting machines																		
8456 30	- Operated by electrodischarge processes																		
	-- Numerically controlled																		
8456 30 11	--- Wire-cut	3.5 %	B3		1.8 %	0.9 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8458	Lathes (including turning centres) for removing metal																		
	- Horizontal lathes																		
8458 11	-- Numerically controlled																		
8458 11 20	--- Turning centres	2.7 %	B3		1.4 %	0.7 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
	--- Automatic lathes																		
8458 11 41	---- Single spindle	2.7 %	B3		1.4 %	0.7 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8458 11 49	---- Multi-spindle	2.7 %	B3		1.4 %	0.7 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8458 11 80	--- Other	2.7 %	B3		1.4 %	0.7 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8482	Ball or roller bearings																		
8482 10	- Ball bearings																		
8482 10 10	-- With greatest external diameter not exceeding 30 mm	8.0 %	B7		6.0 %	5.0 %	4.0 %	3.0 %	2.0 %	1.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8482 10 90	-- Other	8.0 %	B7		6.0 %	5.0 %	4.0 %	3.0 %	2.0 %	1.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %
8482 20 00	- Tapered roller bearings, including cone and tapered roller assemblies	8.0 %	B7		6.0 %	5.0 %	4.0 %	3.0 %	2.0 %	1.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %	0.0 %