HS Code	Product Description	Base Rate	Year 1	Year 2	Year 3	Year 4	Year 5	Year 6	Year 7	Year 8	Year 9	Year 10	Year 11	Year 12	Year 13	Year 14	Year 15	Year 16	Year 17	Year 18	Year 19	Year 20	Year 21	Year 22	Year 23 and Subsequent Years
7215.50	- Other, not further worked than cold-formed or cold-finished:																								
7215.50.10.00	- - Containing by weight 0.6% or more of carbon, other than of circular cross-section	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- - Other:																								
7215.50.91.00	- - - Of a kind used for concrete reinforcement (rebars)	10.0%	9.2%	8.6%	7.9%	7.3%	6.6%	5.9%	5.3%	4.6%	4.0%	3.3%	2.6%	2.0%	1.3%	0.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7215.50.99.00	- - - Other	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7215.90	- Other:																								
7215.90.10.00	- - Of a kind used for concrete reinforcement (rebars)	10.0%	9.2%	8.6%	7.9%	7.3%	6.6%	5.9%	5.3%	4.6%	4.0%	3.3%	2.6%	2.0%	1.3%	0.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7215.90.90.00	- - Other	5.0%	4.6%	4.3%	4.0%	3.6%	3.3%	3.0%	2.6%	2.3%	2.0%	1.7%	1.3%	1.0%	0.7%	0.3%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
72.16	**Angles, shapes and sections of iron or non-alloy steel.**																								
7216.10.00.00	- U, I or H sections, not further worked than hot-rolled, hot-drawn or extruded, of a height of less than 80 mm	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- L or T sections, not further worked than hot-rolled, hot-drawn or extruded, of a height of less than 80 mm:																								
7216.21.00.00	- - L sections	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.22.00.00	- - T sections	15.0%	14.0%	13.0%	12.0%	11.0%	10.0%	9.0%	8.0%	7.0%	6.0%	5.0%	4.0%	3.0%	2.0%	1.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
	- U, I or H sections, not further worked than hot-rolled, hot-drawn or extruded of a height of 80 mm or more:																								
7216.31.00.00	- - U sections	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.32.00.00	- - I sections	15.0%	14.0%	13.0%	12.0%	11.0%	10.0%	9.0%	8.0%	7.0%	6.0%	5.0%	4.0%	3.0%	2.0%	1.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7216.33.00.00	- - H sections	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.40.00.00	- L or T sections, not further worked than hot-rolled, hot-drawn or extruded, of a height of 80 mm or more	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.50	- Other angles, shapes and sections, not further worked than hot-rolled, hot-drawn or extruded:																								
7216.50.10.00	- - Of a height of less than 80 mm	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.50.90.00	- - Other	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- Angles, shapes and sections, not further worked than cold-formed or cold-finished:																								
7216.61.00.00	- - Obtained from flat-rolled products	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7216.69.00.00	- - Other	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- Other:																								
7216.91.00.00	- - Cold-formed or cold-finished from flat-rolled products	15.0%	14.0%	13.0%	12.0%	11.0%	10.0%	9.0%	8.0%	7.0%	6.0%	5.0%	4.0%	3.0%	2.0%	1.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7216.99.00.00	- - Other	15.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
72.17	**Wire of iron or non-alloy steel.**																								
7217.10	- Not plated or coated, whether or not polished:																								
7217.10.10.00	- - Containing by weight less than 0.25% of carbon	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- - Containing by weight 0.25% or more but less than 0.6% of carbon:																								
7217.10.22.00	- - - Bead wire; reed wire; prestressed concrete steel wire; free-cutting steel wire	10.0%	9.2%	8.6%	7.9%	7.3%	6.6%	5.9%	5.3%	4.6%	4.0%	3.3%	2.6%	2.0%	1.3%	0.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.10.29.00	- - - Other	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- - Containing by weight 0.6% or more of carbon:																								
7217.10.31	- - - Spokes wire; bead wire; reed wire; prestressed concrete steel wire; free-cutting steel wire:																								
7217.10.31.10	- - - - Prestressed concrete steel wire	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.10.31.90	- - - - Other	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.10.39.00	- - - Other	12.5%	11.6%	10.8%	10.0%	9.1%	8.3%	7.5%	6.6%	5.8%	5.0%	4.2%	3.3%	2.5%	1.7%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.20	- Plated or coated with zinc:																								
7217.20.10	- - Containing by weight less than 0.25% carbon:																								
7217.20.10.10	- - - Zinc coated with a layer weight of not less than 240 g/m²	7.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.20.10.90	- - - Other	7.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.20.20.00	- - Containing by weight 0.25% or more but less than 0.45% of carbon	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- - Containing by weight 0.45% or more of carbon:																								

HS Code	Product Description	Base Rate	Year 1	Year 2	Year 3	Year 4	Year 5	Year 6	Year 7	Year 8	Year 9	Year 10	Year 11	Year 12	Year 13	Year 14	Year 15	Year 16	Year 17	Year 18	Year 19	Year 20	Year 21	Year 22	Year 23 and Subsequent Years
7217.20.91.00	- - - Steel core wire of a kind used for steel reinforced aluminium conductors (ACSR)	10.0%	9.2%	8.6%	7.9%	7.3%	6.6%	5.9%	5.3%	4.6%	4.0%	3.3%	2.6%	2.0%	1.3%	0.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.20.99.00	- - - Other	10.0%	9.2%	8.6%	7.9%	7.3%	6.6%	5.9%	5.3%	4.6%	4.0%	3.3%	2.6%	2.0%	1.3%	0.7%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.30	- Plated or coated with other base metals:																								
	- - Containing by weight less than 0.25% of carbon:																								
7217.30.11.00	- - - Plated or coated with tin	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.30.19.00	- - - Other	12.5%	11.6%	10.8%	10.0%	9.1%	8.3%	7.5%	6.6%	5.8%	5.0%	4.2%	3.3%	2.5%	1.7%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
	- - Containing by weight 0.25% or more of carbon but less than 0.6% of carbon:																								
7217.30.21.00	- - - Plated or coated with tin	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.30.29.00	- - - Other	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	- - Containing by weight 0.6% or more of carbon:																								
7217.30.31	- - - Copper alloy coated steel wire of a kind used in the manufacture of pneumatic rubber tyres (bead wire):																								
7217.30.31.10	- - - - Coated with brass	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.30.31.90	- - - - Coated with other copper alloys	5.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.30.32.00	- - - Other, plated or coated with tin	12.5%	11.6%	10.8%	10.0%	9.1%	8.3%	7.5%	6.6%	5.8%	5.0%	4.2%	3.3%	2.5%	1.7%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7217.30.39.00	- - - Other	12.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.90	- Other:																								
7217.90.10.00	- - Containing by weight less than 0.25% of carbon	5.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7217.90.90.00	- - Other	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
	III. - STAINLESS STEEL																								
72.18	**Stainless steel in ingots or other primary forms; semi-finished products of stainless steel.**																								
7218.10.00.00	- Ingots and other primary forms	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
	- Other:																								
7218.91.00.00	- - Of rectangular (other than square) cross-section	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7218.99.00.00	- - Other	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
72.19	**Flat-rolled products of stainless steel, of a width of 600 mm or more.**																								
	- Not further worked than hot-rolled, in coils:																								
7219.11.00.00	- - Of a thickness exceeding 10 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.12.00.00	- - Of a thickness of 4.75 mm or more but not exceeding 10 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.13.00.00	- - Of a thickness of 3 mm or more but less than 4.75 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.14.00.00	- - Of a thickness of less than 3 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
	- Not further worked than hot-rolled, not in coils:																								
7219.21.00.00	- - Of a thickness exceeding 10 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.22.00.00	- - Of a thickness of 4.75 mm or more but not exceeding 10 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.23.00.00	- - Of a thickness of 3 mm or more but less than 4.75 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.24.00.00	- - Of a thickness of less than 3 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
	- Not further worked than cold-rolled (cold-reduced):																								
7219.31.00.00	- - Of a thickness of 4.75 mm or more	7.5%	7.4%	6.6%	5.8%	5.0%	4.1%	3.3%	2.5%	1.6%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7219.32.00.00	- - Of a thickness of 3 mm or more but less than 4.75 mm	7.5%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7219.33.00.00	- - Of a thickness exceeding 1 mm but less than 3 mm	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7219.34.00.00	- - Of a thickness of 0.5 mm or more but not exceeding 1 mm	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7219.35.00.00	- - Of a thickness of less than 0.5 mm	10.0%	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
7219.90.00.00	- Other	7.5%	7.4%	6.6%	5.8%	5.0%	4.1%	3.3%	2.5%	1.6%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
72.20	**Flat-rolled products of stainless steel, of a width of less than 600 mm.**																								
	- Not further worked than hot-rolled:																								
7220.11	- - Of a thickness of 4.75 mm or more:																								
7220.11.10.00	- - - Hoop and strip, of a width not exceeding 400 mm	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7220.11.90.00	- - - Other	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
7220.12	- - Of a thickness of less than 4.75 mm:																								