| HS Code | Product Description | Base Rate | Year 1 | Year 2 | Year 3 | Year 4 | Year 5 | Year 6 | Year 7 | Year 8 | Year 9 | Year 10 | Year 11 | Year 12 | Year 13 | Year 14 | Year 15 | Year 16 | Year 17 | Year 18 | Year 19 | Year 20 and Subsequent Years |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4006.10.01 | -- Of natural gums | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4006.10.09 | -- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4006.90** | **- Other:** | | | | | | | | | | | | | | | | | | | | | |
| 4006.90.01 | -- Tubes | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4006.90.09 | -- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4007** | **Vulcanised rubber thread and cord.** | | | | | | | | | | | | | | | | | | | | | |
| 4007.00.00 | Vulcanised rubber thread and cord | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4008** | **Plates, sheets, strip, rods and profile shapes, of vulcanised rubber other than hard rubber:** | | | | | | | | | | | | | | | | | | | | | |
| | **- Of cellular rubber:** | | | | | | | | | | | | | | | | | | | | | |
| **4008.11** | **-- Plates, sheets and strip:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Flooring:** | | | | | | | | | | | | | | | | | | | | | |
| 4008.11.01 | ---- Mats, rectangular, made by cutting from the piece | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.11.09 | ---- Underlay of rubber | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.11.19 | ---- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.11.29 | --- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.19.00 | -- Other | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Of non-cellular rubber:** | | | | | | | | | | | | | | | | | | | | | |
| **4008.21** | **-- Plates, sheets and strip:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Flooring:** | | | | | | | | | | | | | | | | | | | | | |
| 4008.21.01 | ---- Mats, rectangular, made by cutting from the piece | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.21.09 | ---- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.21.19 | --- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4008.29.00 | -- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4009** | **Tubes, pipes and hoses, of vulcanised rubber other than hard rubber, with or without their fittings (for example, joints, elbows, flanges):** | | | | | | | | | | | | | | | | | | | | | |
| | **- Not reinforced or otherwise combined with other materials:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.11.00 | -- Without fittings | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4009.12** | **-- With fittings:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Hydraulic brake hoses:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.12.11 | ---- Automotive brake hoses | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.12.14 | ---- Other | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.12.19 | --- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Reinforced or otherwise combined only with metal:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.21.00 | -- Without fittings | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4009.22** | **-- With fittings:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Hydraulic brake hoses:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.22.11 | ---- Automotive brake hoses | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.22.14 | ---- Other | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.22.19 | --- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Reinforced or otherwise combined only with textile materials:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.31.00 | -- Without fittings | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4009.32** | **-- With fittings:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Hydraulic brake hoses:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.32.11 | ---- Automotive brake hoses | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.32.14 | ---- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.32.19 | --- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Reinforced or otherwise combined with other materials:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.41.00 | -- Without fittings | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4009.42** | **-- With fittings:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Hydraulic brake hoses:** | | | | | | | | | | | | | | | | | | | | | |
| 4009.42.11 | ---- Automotive brake hoses | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.42.14 | ---- Other | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4009.42.19 | --- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4010** | **Conveyor or transmission belts or belting, of vulcanised rubber:** | | | | | | | | | | | | | | | | | | | | | |
| | **- Conveyor belts or belting:** | | | | | | | | | | | | | | | | | | | | | |
| 4010.11.00 | -- Reinforced only with metal: | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.12.00 | -- Reinforced only with textile material | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % |
| 4010.19.00 | -- Other | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Transmission belts or belting:** | | | | | | | | | | | | | | | | | | | | | |
| 4010.31.00 | -- Endless transmission belts of trapezoidal cross-section (V-belts), V-ribbed, of an outside circumference exceeding 60 cm but not exceeding 180 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |

| HS Code | Product Description | Base Rate | Year 1 | Year 2 | Year 3 | Year 4 | Year 5 | Year 6 | Year 7 | Year 8 | Year 9 | Year 10 | Year 11 | Year 12 | Year 13 | Year 14 | Year 15 | Year 16 | Year 17 | Year 18 | Year 19 | Year 20 and Subsequent Years |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4010.32.00 | -- Endless transmission belts of trapezoidal cross-section (V-belts), other than V-ribbed, of an outside circumference exceeding 60 cm but not exceeding 180 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.33.00 | -- Endless transmission belts of trapezoidal cross-section (V-belts), V-ribbed, of an outside circumference exceeding 180 cm but not exceeding 240 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.34.00 | -- Endless transmission belts of trapezoidal cross-section (V-belts), other than V-ribbed, of an outside circumference exceeding 180 cm but not exceeding 240 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.35.00 | -- Endless synchronous belts, of an outside circumference exceeding 60 cm but not exceeding 150 cm | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.36.00 | -- Endless synchronous belts, of an outside circumference exceeding 150 cm but not exceeding 198 cm | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % |
| **4010.39** | **-- Other:** | | | | | | | | | | | | | | | | | | | | | |
| 4010.39.11 | --- Belts and belting, cogged, toothed or otherwise adapted for the timing of mechanical or electrical functions | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4010.39.19 | --- Other | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % | 2.5 % |
| **4011** | **New pneumatic tyres, of rubber:** | | | | | | | | | | | | | | | | | | | | | |
| **4011.10** | **- Of a kind used on motor cars (including station wagons and racing cars):** | | | | | | | | | | | | | | | | | | | | | |
| 4011.10.01 | -- For use in the assembly of motor vehicles as may be determined by the Minister in accordance with section 14 of this Act | 10.0 % | 9.0 % | 8.0 % | 7.0 % | 6.0 % | 5.0 % | 4.0 % | 3.0 % | 2.0 % | 1.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.10.09 | -- Other | 5.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4011.20** | **- Of a kind used on buses or lorries:** | | | | | | | | | | | | | | | | | | | | | |
| | **-- For use in the assembly of motor vehicles as may be determined by the Minister in accordance with section 14 of this Act** | | | | | | | | | | | | | | | | | | | | | |
| 4011.20.03 | --- Internal rim diameter less than 495 mm | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % | 5.0 % |
| 4011.20.07 | --- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **-- Other:** | | | | | | | | | | | | | | | | | | | | | |
| 4011.20.12 | --- Internal rim diameter less than 495 mm | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.20.18 | --- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.30.00 | - Of a kind used on aircraft | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.40.00 | - Of a kind used on motorcycles | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.50.00 | - Of a kind used on bicycles | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Other, having a "herring-bone" or similar tread:** | | | | | | | | | | | | | | | | | | | | | |
| 4011.61.00 | -- Of a kind used on agricultural or forestry vehicles and machines | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.62.00 | -- Of a kind used on construction or industrial handling vehicles and machines and having a rim size not exceeding 61 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.63.00 | -- Of a kind used on construction or industrial handling vehicles and machines and having a rim size exceeding 61 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4011.69** | **-- Other:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Of a kind used on light commercial vehicles:** | | | | | | | | | | | | | | | | | | | | | |
| 4011.69.11 | ---- Internal rim diameter less than 508 mm | 5.0 % | 4.7 % | 4.3 % | 4.0 % | 3.7 % | 3.3 % | 3.0 % | 2.7 % | 2.3 % | 2.0 % | 1.7 % | 1.3 % | 1.0 % | 0.7 % | 0.3 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.69.16 | ---- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.69.19 | --- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| | **- Other:** | | | | | | | | | | | | | | | | | | | | | |
| 4011.92.00 | -- Of a kind used on agricultural or forestry vehicles and machines | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.93.00 | -- Of a kind used on construction or industrial handling vehicles and machines and having a rim size not exceeding 61 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.94.00 | -- Of a kind used on construction or industrial handling vehicles and machines and having a rim size exceeding 61 cm | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4011.99** | **-- Other:** | | | | | | | | | | | | | | | | | | | | | |
| | **--- Of a kind used on light commercial vehicles:** | | | | | | | | | | | | | | | | | | | | | |
| 4011.99.11 | ---- Internal rim diameter less than 508 mm | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.99.14 | ---- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4011.99.19 | --- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4012** | **Retreaded or used pneumatic tyres of rubber; solid or cushion tyres, tyre treads and tyre flaps, of rubber:** | | | | | | | | | | | | | | | | | | | | | |
| | **- Retreaded tyres:** | | | | | | | | | | | | | | | | | | | | | |
| **4012.11** | **-- Of a kind used on motor cars (including station wagons and racing cars):** | | | | | | | | | | | | | | | | | | | | | |
| 4012.11.11 | --- Internal rim diameter less than 508 mm | 5.0 % | 4.5 % | 4.0 % | 3.5 % | 3.0 % | 2.5 % | 2.0 % | 1.5 % | 1.0 % | 0.5 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4012.11.19 | --- Other | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4012.12.00 | -- Of a kind used on buses or lorries | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| 4012.13.00 | -- Of a kind used on aircraft | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % | 0.0 % |
| **4012.19** | **-- Other:** | | | | | | | | | | | | | | | | | | | | | |